

9-30725

AirSense Stratos Micra 10 High Sensitivity Smoke Detector

Description

The AirSense Micra 10 is designed to provide very high sensitivity smoke detection in a small package.

ClassiFire Perceptive Artificial Intelligence ensures that the detector operates at optimum sensitivity for the protected environment, without the need for complex setup. This means the product will configure itself to provide high sensitivity in a computer room or reduced sensitivity in a smoky area.

The detector is designed to fit into a Docking Station. All sampling pipes and cables are connected to the Docking Station as a first fix operation leaving the detector to be fitted during the final commissioning phase if required. This ensures that detectors are less likely to be damaged during the installation.

Upgradable volt-free Fire and Fault relay outputs are available for remote monitoring by local fire detection or BMS systems.

Typical Applications

- Data storage units
- Prison cells
- Plant rooms
- Air conditioning units
- Equipment racks
- Computer rooms
- Air duct protection
- Heritage property protection
- Critical equipment
- Anti-smoking enforcement
- Motor rooms

Options Available

- Addressable Protocol Interface Cards APIC™ available
- Relay expansion card



Details

- Ultra small low cost aspirating smoke detector for easy and discreet installation
- High sensitivity provided by laser based forward light scatter for reliable early warning
- Single sampling pipe up to 50m in length (still air)
- Unique ClassiFire® Perceptive Artificial Intelligence system that dynamically adjusts the detector's operating parameters, allowing for day to day changes in the protected environment and dust separation system contamination
- Unwanted alarms from dust are avoided using patented Dual Technology LDD 3D3 Laser Dust Discrimination and elimination system
- CPR approved

9-30725

AirSense Stratos Micra 10 High Sensitivity Smoke Detector

Technical specifications

Electrical

Operating voltage	21.6 to 26.4 VDC
Current consumption	250 mA

Detection

Detection principle	Laser light scattering mass detection and particle evaluation
---------------------	---

Particle sensitivity range 0.003 μ to 10 μ

Detection principle	Laser light scattering mass detection and particle evaluation
---------------------	---

Particle sensitivity range 0.003 μ to 10 μ

Sensitivity range 0.3% to 25%
(%Obs/m)

Alarm levels 4 (Aux, Pre-alarm, Alarm and Alarm 2)

Physical

Physical dimensions 145 x 220 x 85 mm (W x H x D)

Net weight 1.7 kg

Colour Cream

Cable entries 2 x M20

Material (body) Sheet steel enclosure

Environmental

Operating temperature -10 to +60°C (EN54-20)

Relative humidity 0 to 90% noncondensing

Environment Indoor

IP rating IP40

Standards & regulation

Certification EN54-20

Sampling pipework

Inlets 1

Length 50m maximum run (25m in moving air)

Diameter 27mm OD

Amount of Class A holes up to 2 holes
(high sensitivity)

Amount of Class B holes up to 4 holes
(enhanced sensitivity)

Amount of Class C holes up to 10 holes
(normal sensitivity)

Exhaust 1 (optional)

Outputs

Standard 2 - Alarm (n/o) and Fault (n/c)

Rating 500mA @ 30V

Expansion Optional input and relay card

User interface

Indicators LED

Networking

SenseNET (RS-485) Not supported
