FIREscape EXIT SIGN LENS 1050710 Compliant

Features

- ▶ Complies with ISO 7010
- Visible at 20 & 40 metres
- Fixes to exit sign frames EL-20(WHT) & EL-40(WHT).



Description

Exit sign lenses designed to fit EL-20(WHT) and EL-40(WHT) exit sign frames.

ISO 7010 compliant and viewable at either 20m or 40m.

Specification

Materials	Pelxiglass-8N
Fire Class	UL94 V-0
Viewing Distance	20m & 40m
Dimensions of sign (mm)	EL-20G (ISO) 200W x 140H x 6D
	EL-40G (ISO) 330W x 225H x 6D
Weight (g)	EL-20G (ISO) 180g
	EL-40G (ISO) 478g

Order Codes

Product

Part Number

You Tube

Exit Sign Down Arrow Lens - 20	EL-20G-D (ISO) (arrow points down)
Exit Sign Left Arrow Lens - 20	EL-20G-L (ISO) (arrow points left)
Exit Sign Right Arrow Lens - 20	EL-20G-R (ISO) (arrow points right)
Exit Sign Up Arrow Lens - 20	EL-20G-U (ISO) (arrow points up)
Exit Sign Down Arrow Lens - 40	EL-40G-D (ISO) (arrow points down)
Exit Sign Left Arrow Lens - 40	EL-40G-L (ISO) (arrow points left)
Exit Sign Right Arrow Lens - 40	EL-40G-R (ISO) (arrow points right)
Exit Sign Up Arrow Lens - 40	EL-40G-U (ISO) (arrow points up)

NHOCHIKI 🗹 in 🔊



Hochiki Europe (UK) Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. to be a complete and up-to-date description.