



L@TITUDE NETWORK VISION ANNUNCIATOR



STANDARD FEATURES

- Full-color 7" (800 x 480 pixel) interface
- · Replicates information displayed at the FACP
- Automatic display brightness adjustment
- Internal buzzer
- · Connects via control panel network terminals
- · Low current, 24V DC powered
- Configurable functionality
- · Enable key-switch
- · Sheet steel enclosure
- Surface or semi-flush enclosure options available

TECHNICAL SPECIFICATIONS

	10110
Supply Voltage Range	21-30V DC
Quiescent Current during Power Failure	216mA typical (buzzer off @ 24V DC) 246mA typical (buzzer on @ 24V DC) 341mA max (buzzer on @ 21V DC)
Maximum Number of Units on a Network	64 Annunciators including one L@titude Panel
Size	9.25" x 6.7" x 2.2" (235mm x 170mm x 55mm)
Display	Full color 800 x 480 LCD with resistive touch screen and automatic back-light dimming
Construction	18 SWG, 1.2mm mild sheet steel
Cable Entry	2 x 20 mm knockouts on top & bottom 4 x 20 mm and 2 x 28 mm knock outs in back
Vision Annunciator Electronics Only	S787
Finish	Epoxy powder coated
Color	Enclosure
	Red (RAL3002)
	Gray (BS 00 A 05)
	●Black (RAL9005)
	Fascia OSignal White (RAL9003)
Optional Semi-Flush Mounting Collar Kit	KM1098RD - Red KM1098GY - Gray KM1098BS - Black
Weight	4.4 lbs (2 kg) maximum
IP Rating	IP 30

DESCRIPTION

The L@titude Network Vision Annunciator is the most qualified annunciator on the market. It is a full-color graphical display and touchscreen. It represents the most versatile annunciator for life safety systems available today. The Annunciator is a full-function fire alarm repeater that is configurable and application flexible for use in applications such as hospital nursing stations and elevator alarms.

L@titude Network Vision Annunciators can be configured to fully replicate fire control panel functionality, or to operate as simple, display-only devices for applications where access to fire alarm controls are inappropriate.

PRODUCT LISTINGS







California State Fire Marshal 7120-0410:0507

Specifications subject to change without notice.

Hochiki America Corporation

7051 Village Drive, Suite 100, Buena Park, CA 90621-2268

Phone: 714-522-2246 Fax: 714-522-2268

Technical Support: 800-845-6692 or technical support@hochiki.com



Find latest revision at www.hochiki.com