

Explosion-Proof IR³ Infra-Red Flame Detector IFD-E(Exd)



Features

- ▶ Unaffected by convection currents, draughts or wind and solar-blind
- ▶ Tolerant of fumes, vapours, dust and mist
- ▶ ATEX certified to EEx d IIC T6 (85 °C) (zones 1, 21, 2 and 22)
- ▶ Responsive to a flame more than 25 m away
- ▶ Selectable response speed
- ▶ Class 1 performance as defined in BS EN54-10:2002 (on the high sensitivity setting)
- ▶ Optical self-test
- ▶ SIL Capable

Description

Model IFD-E(Exd) is an Explosion-Proof IR³ flame detector designed for use where open flaming fires may be expected and responds to the light emitted from flames during combustion.

The detector discriminates between flames and other light sources by responding only to particular optical wavelengths and flame flicker frequencies. This enables the detector to avoid false alarms due to such factors as flickering sunlight. Ideal for the detection of flames from the burning of Aviation Fuels (kerosene), Butane, Grain & Feeds, Hydrogen, Paper, Natural Gas, Petrol (gasoline) etc.

Specification

Ordering codes	IFD-E(Exd)	
	IFD-MB (Stainless Steel Mounting Bracket)	
Operating voltage	14 – 30 V dc	
Alarm Current (selected via by DIL switches)	3 ~ 28 mA	
Test Signal Voltage	14 to 30 V dc	
Relay Contact Ratings	Current	1 A (max)
	Voltage	50 V dc (max)
	Power	30 W (max) (resistive loads only)
Power Up Time	2 seconds (max)	
Field of View	90° min. Cone	
Range	Class 1 – 0.1 m ² n-heptane at 25 m Class 3 – 0.1 m ² n-heptane at 12 m	
Operating Wavelength Band	IR (0.75 ~ 2.7 μm)	
Operating temperature range	-10 °C to + 55 °C (sensor limit -10 °C to +40 °C (T4))	
Storage temperature range	-20 °C to + 65 °C	
Maximum humidity	95% RH Non condensing	
Ingress Protection Rating	IP66	
Colour / Case Material	Red / Copper Free Aluminium Alloy LM25	
Weight (Kg)/Height/Width/Depth (mm)	2.5 / 150 / 146 / 137	

Hochiki Europe (UK) Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. to be a complete and up-to-date description.