Dual Switch Manual Call Point



D		
Prod	uct overview	7

Product Type Dual Switch Manual Call Point
Part No. SA5900-011APO (Green)

Product information

The Dual Switch Manual Call Point provides volt free double pole change-over contacts suitable for normally open or normally closed multiple switching from a single activation point. The device is activated by pressing the resettable element. An activation status is indicated through the rotation of the resettable element, displaying yellow and black indication bars. The manual call point can be easily reset from the front using the supplied reset key.

- · Resettable operating element
- · Easy access, front reset mechanism
- Ergonomic reset key
- Double pole change-over contacts
- · Suitable for semi flush or surface mounting
- · Optional transparent hinged cover

Technical data

Supply voltage 0-33V DC (Vmin–Vmax)

Switch contact type Volt Free Double pole change-

over

Switch contact type 2A

Operating temperature -40°C to 70°C

Humidity 0% to 95%RH

(no condensation or icing)

IP Rating IP44

Dimensions 90mm height x 90mm width x

63mm depth

Weight 180g

Electrical Consideration

The Dual Switch Manual Call Point has a contact rating of 33V DC at 2A.

Mechanical Construction

The component parts of the Dual Switch Manual Call Point are moulded in a robust fire retardant polycarbonate.

EMC Directive 2004/108/EC

The Dual Switch Manual Call Point complies with the essential requirements of the EMC Directive 2004/108/EC, provided that it is used as described in this datasheet.

A copy of the Declaration of Conformity is available from Apollo on request.

Conformity of the Dual Switch Manual Call Point with the EMC Directive does not confer compliance with the directive on any apparatus or systems connected to it.

36 Brookside Road, Havant, Hampshire PO9 1JR, UK. Tel: +44 (0)23 9249 2412 Fax: +44 (0)23 9249 2754 Email: sales@apollo-fire.com Web: www.apollo-fire.co.uk

















