

# Solo Smoke Detector Tester SAFETY DATA SHEET

**SDS0086UK** 

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH) & 2015/830

#### SECTION 1: IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product identifier

**Product Name** Solo Smoke Detector Tester

Trade Name Solo A5-XXX (XXX denotes customer variant)

CAS No. Mixture EINECS No. Mixture REACH Registration No. None assigned.

Relevant identified uses of the substance or mixture and uses advised against 1.2

Identified Use(s) Smoke simulation Uses Advised Against None known.

1.3 Details of the supplier of the safety data sheet

> Company Identification Detectortesters (No Climb Products Ltd)

Edison House, 163 Dixons Hill Road, Welham Green, Hertfordshire. AL9 7JE. United

Kingdom

Telephone +44 (0) 1707 282760 Fax +44 (0) 1707 282777 SDS@detectortesters.com E-Mail (competent person)

**Emergency telephone number** 

Emergency Phone No. +44 (0) 1707 282760

#### **SECTION 2: HAZARDS IDENTIFICATION**

2.1 Classification of the substance or mixture

Regulation (EC) No. 1272/2008 (CLP)

Aerosol 1; Extremely flammable aerosol. Pressurised container: May burst if heated.

2.2 Label elements

Hazard Pictogram(s) According to Regulation (EC) No. 1272/2008 (CLP)



GHS02

Signal Word(s) Danger.

Hazard Statement(s) H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Precautionary Statement(s) P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211: Do not spray on an open flame or other ignition source. P251: Pressurised container - Do not pierce or burn, even after use.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50°C.

2.3 Other hazards

#### **SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

Product as supplied: Aerosol.

3.1 Substances

EC Classification No. 1272/2008								
Hazardous Ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard Pictogram(s) and Hazard Statement(s)			
Butane	50-100	106-97-8	203-448-7	01-2119474691-32	GHS02, Flam. Gas 1; H220, GHS04, Press. Gas: Liquefied gas; H280			
Propane	10-25	74-98-6	200-827-9	01-2119486944-21	GHS02, Flam. Gas 1; H220, GHS04, Press. Gas: Liquefied gas; H280			
Ethanol	0-5	64-17-5	200-578-6	01-2119457610-43	GHS02, Flam. Liq. 2; H225; Eye Irrit. 2, H319			

3.3 Additional Information

For full text of H/P Statements see section 16.

#### **SECTION 4: FIRST AID MEASURES**



Description of first aid measures

Inhalation If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable

for breathing. Skin Contact Wash skin with water.

Flush eyes with water for at least 15 minutes while holding eyelids open. **Eye Contact** 

Ingestion Unlikely route of exposure.

Most important symptoms and effects, both acute and delayed

None anticipated.

Date: 13 June 2018 Revision: 5 Page: 1/5



## Solo Smoke Detector Tester

4.3 Indication of any immediate medical attention and special treatment needed Unlikely to be required but if necessary treat symptomatically.

#### **SECTION 5: FIREFIGHTING MEASURES**

Pressurised container: May burst if heated.

5.1 Extinguishing media
Suitable Extinguishing media

Unsuitable extinguishing media

5.2 Special hazards arising from the substance or mixture

5.3 Advice for fire-fighters

Extinguish with carbon dioxide, dry chemical, foam or waterspray.

Do not use water jet.

Heating may cause pressure rise with risk of bursting.

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because

they are likely to rupture under fire conditions.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

The product is an aerosol. It is unlikely to present spillage or leakage hazard. In case of rupture, released content should be contained as any other solvent spill.

6.1 Personal precautions, protective equipment and emergency procedures

6.2 Environmental precautions

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

Ensure adequate ventilation. Wear suitable gloves and eye/face protection.

Do not release large quantities into the surface water or into drains. Collect mechanically and dispose of according to Section 13.

Absorb spillage in earth or sand. Transfer to a lidded container for disposal or recovery.

Containers must not be punctured or destroyed by burning, even when empty.

See Also Section 8 and 13

#### **SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Provide adequate ventilation. Do not eat, drink or smoke during work. Wash

hands thoroughly after handling.

7.2 Conditions for safe storage, including any

incompatibilities
Storage temperature

Observe official regulations on storing packagings with pressurised containers.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding

No personal respiratory protective equipment normally required. Handling of larger amounts: In case of insufficient ventilation, wear suitable respiratory equipment. A suitable mask with filter type A (EN14387 or EN405) may be appropriate.

50 dea C.

Storage life Considered stable under normal conditions.

Incompatible materials

Specific end use(s)

None anticipated.

Smoke simulation

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1 Control parameters

7.3

8.1.1 Occupational Exposure Limits

SUBSTANCE.	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m³)	STEL (ppm)	STEL (mg/m³)	Note
Butane	106-97-8	600	1450	750	1810	WEL
Ethanol	64-17-5	1000	1920	-	-	WEL

WEL: Workplace Exposure Limit (UK HSE EH40)

8.1.2 Biological limit value Not established.
8.1.3 PNECs and DNELs Not established.

**8.2 Exposure controls** Provide adequate ventilation.

8.2.1 Appropriate engineering controls

8.2.2 Personal protection equipment

Eye/ face protection If eye contact is likely: Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)

Wear suitable gloves if prolonged skin contact is likely. Gloves: Nitrile rubber.



Respiratory protection

Thermal hazards Not applicable.

**8.2.3** Environmental Exposure Controls Do not release large quantities into the surface water or into drains.

Revision: 5 Page: 2/5 Date: 13 June 2018



#### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Information on basic physical and chemical properties

Aerosol. Appearance Colour. Colourless. Odour Characteristic. Odour Threshold (ppm) Not determined. pH (Value) Not determined. Melting Point (°C) / Freezing Point (°C) Not determined.

Boiling point/boiling range (°C): -44 °C Flash Point (°C) Not applicable Not available.

Evaporation rate Flammability (solid, gas) Extremely flammable.

Upper/lower flammability or explosive limits Explosive Limit RangesExplosive Limit Ranges: 1.5-10.9 Vol-%

Vapour pressure 3.8 bar @20 °C Density 0.58 g/cm3 @20 °C Vapour density Not determined. Relative density Not determined. Solubility(ies) Immiscible with water. Partition Coefficient (n-Octanol/water) Not determined.

Ignition temperature 365°C

Auto Ignition Point (°C) Product is not selfianiting

Decomposition Temperature (°C) Not determined. Kinematic Viscosity Viscosity (mPa. s) Not determined. Explosive properties Not explosive. Oxidising properties Not oxidising.

9.2 Other information

Organic solvents - Content 98.9%

#### **SECTION 10: STABILITY AND REACTIVITY**

10.1 Reactivity Stable under normal conditions. 10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions No hazardous reactions known if used for its intended purpose.

Conditions to avoid Heat and direct sunlight. 10.4 10.5 Incompatible materials None anticipated.

Hazardous decomposition product(s) No hazardous decomposition products known. 10.6

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

11.1 Information on toxicological effects

> Acute toxicity Low acute toxicity. Hazard label(s) Non-irritant. Serious eye damage/irritation Not classified.

Respiratory or skin sensitization It is not a skin sensitiser.

Germ cell mutagenicity There is no evidence of mutagenic potential.

Carcinogenicity No evidence of carcinogenicity.

Reproductive toxicity None anticipated. STOT - single exposure Not classified Not classified STOT - repeated exposure Aspiration hazard None anticipated.

11.2 Other information None.

#### **SECTION 12: ECOLOGICAL INFORMATION**

Low toxicity to aquatic organisms.

The product is readily biodegradable. Unlikely to persist. 12.2 Persistence and degradability The product has no potential for bioaccumulation. 12.3 Bioaccumulative potential

Mobility in soil Immiscible with water. The product is predicted to have low mobility in soil. 12.4

Results of PBT and vPvB assessment Not classified as PBT or vPvB. 12.5

Other adverse effects 12.6 None.

### **SECTION 13: DISPOSAL CONSIDERATIONS**

13.1 Waste treatment methods Recycle only completely emptied packaging. Containers must not be punctured or

destroyed by burning, even when empty. Non-emptied aerosol: Dispose of wastes in an

approved waste disposal facility. Do NOT landfill.

**UN 1950** 

13.2 **Additional Information** Disposal should be in accordance with local, state or national legislation.

EAL 7055 Aerosol spray can

#### **SECTION 14: TRANSPORT INFORMATION**

**UN** number

ADR Classification CodelMDG, IATA Label

**UN proper shipping name** 14.2

Date: 13 June 2018 Revision: 5 Page: 3/5



## Solo Smoke Detector Tester

**IMDG** IATA Label

14.3 Transport hazard class(es)

ADR Group

**ADR Group** 

Class /Classification LabelADR-RID Labels IMDG, IATA Label

Class / Division Label

Hazard label(s)

Packing group

ADR Classification CodelMDG, IATA Label

14.5 **Environmental hazards** 

**Marine Pollutant** 

14.6 Special precautions for user

> Kemler Code IMDG EMS

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the

**IBC Code** 

14.8 **Additional Information** 

**ADR Classification Code** 

Limited Quantity (LQ)

**ADR Transport Category Tunnel Restriction Code** 

**IMDG** 

Limited Quantity (LQ)

IATA Label

Limited Quantity (LQ)

1950 AEROSOLS **AEROSOLS** 

AEROSOLS, Flammable

2 5F Gases

2.1

2.1

2.1

None.

Warning: Gases

F-D, S-U

Not applicable.



Not applicable in Limited Quantities.





UN1950, AEROSOLS, 2.1

**UN Model Regulation** 

### **SECTION 15: REGULATORY INFORMATION**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1 **EU regulations**

Authorisations and / or Restrictions On Use

Candidate List of Substances of Very High Concern for Authorisation REACH: ANNEX XVII restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and

REACH: ANNEX XIV list of substances subject to authorisation Community Rolling Action Plan (CoRAP)

**National regulations** 15.1.2

Wassergefährdungsklasse (Germany)

Ethanol

Technical Instructions (air)

VOC-CH VOC-EU

Danish MAL Code

15.2 **Chemical Safety Assessment** 

All chemicals are not listed All chemicals are not listed

All chemicals are not listed All chemicals are not listed None known.

#### WGK class 1

Class	Share in %
NK	50 – 100

98.93% 569.8g/l 3-1

Not available.



# Solo Smoke Detector Tester

#### **SECTION 16: OTHER INFORMATION**

The following sections contain revisions or new statements: 3, 9.

**LEGEND** 

LTEL Long Term Exposure Limit
STEL Short Term Exposure Limit
STOT Specific Target Organ Toxicity
DNEL Derived No Effect Level

PNEC Predicted No Effect Concentration
PBT Persistent, Bioaccumulative and Toxic
vPvB very Persistent and very Bioaccumulative
WGK Wassergefährdungsklasse (Germany)
VOC Volatile Organic Compounds

MAL Code Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

ADR Accord européen elative au transport international des marchandises dangereuse par route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG International Maritime Code for Damgerous Goods

IATA International Air Transport Association

Press. Gas Gases under pressure

Flam. Gas 1 Flammable gas.Flammable gas Category 1

Hazard Statement(s)

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

#### **Disclaimers**

The information is based on the best knowledge of No Climb Products Ltd. and its advisors and is given in good faith, but we cannot guarantee its accuracy, reliability or completeness and therefore disclaim any liability for loss or damage arising out of use of this data. Since conditions of use are outside the control of the Company and its advisors we disclaim any liability for loss or damage when the product is used for purposes other than it is intended.

#### Annex to the extended Safety Data Sheet (eSDS)

No information available.

Revision: 5 Page: 5/5 Date: 13 June 2018