



# YBO-BS/SIL

## Analogue Addressable Base Sounder

### Features

- ▶ Loop powered with single loop address - addressed automatically by Control Panel or via the TCH-B200 Hand Held Programmer
- ▶ Variable sound output 50 ~ 98 dB(A) ( $\pm 2$  dB(A)) output at 1 metre
- ▶ Fits Hochiki Standard and supports ESP Sensors, Addressable Beacons and Addressable Remote Indicator
- ▶ 51 User-Selectable Tones (all tones EN54-3 compatible)
- ▶ Approved by LPCB & VdS
- ▶ SIL Level 2 approved

### Description

Model YBO-BS/SIL is an addressable loop powered Base Sounder innovatively designed to give a range of tones and volumes with a maximum output of up to 98 dB(A) ( $\pm 2$  dB(A)) with low current consumption. The unit is designed to fit to the Standard Base (YBNR/3(WHT)) and can be fitted with any of the FIREscape+ Range of Sensors, Beacons or Remote Indicators. The unit can also be converted into a wall sounder with the simple addition of a Cap (SI/CAP). The sounder is Ingress Protection rated to IP21 and for internal use only.



### Specification

Operating Voltage	17 ~ 41 VDC
Low Power Mode (typ)	40 $\mu$ A
Quiescent Current (typ)	150 $\mu$ A
Sounding Current (typ)	0.8 mA (50 dB(A) @ 1 m) ~ 16 mA (98 dB(A) @ 1 m)
Sound Output (at 1 metre)	50 ~ 98 dB(A) ( $\pm 2$ dB(A)) @ 24 VDC or above (EN54-3 compliant)
Number of Tones	51
Tone Frequency Range	300 Hz ~ 2850 Hz
Operating Temperature Range	-10 °C to +50 °C
Storage Temperature Range	-30 °C to +70 °C
Maximum Humidity	95% RH - Non Condensing (at 40 °C)
Colour / Case Material	Ivory or white / PC+PS+GF5
Ingress Protection Rating	IP21
Weight (g) / Dimensions (mm)	112 / H113 x W113 x D43
Base Fixing Centres (mm)	48 ~ 74

Note: Although the TCH-B200 Hand Held Programmer will allow addresses between 128 and 254 to be programmed into the YBO-BS, addresses 1 to 127 ONLY should be used.

### Ordering Codes

#### Product

SIL Approved 2 Base Sounder Beacon

SIL Approved 2 Base Sounder Beacon - White Case

#### Part Number

YBO-BS/SIL

YBO-BS(WHT)/SIL



For further information visit [www.hochikieurope.com/silapproved](http://www.hochikieurope.com/silapproved)

Hochiki Europe (UK) Ltd. reserves the right to alter the specification of its products from time to time without notice. Although every effort has been made to ensure the accuracy of the information contained in this document it is not warranted or represented by Hochiki Europe (UK) Ltd. to be a complete and up-to-date description.