

# Zenith

versione/version:01/2018

**BATTERIA SIGILLATA AGM  
AGM MAINTENANCE FREE BATTERY**

# ZGL120034



CHARACTERISTIC / CARATTERISTICHE	
Volt	12V
Capacity / Capacità	20h 18Ah
	5h 16Ah
Internal Resistance	Full Charged Battery 25°C ≤16mΩ
Capacity affected by Temperature / Effetti delle temperature sulla capacità	40°C 102%
	25°C 100%
	0°C 85%
	-15° 65%
Self-Discharge 25°C Capacity / Autoscarica a 25°C	after 3 month storage 90%
	after 6 month storage 80%
	after 12 month storage 62%
Charge (Costant Voltage 25°C)	Float Volt 13.6 - 13.8V
	Charge Max.6.8Amp. 14.4 - 15 Volt

CHARACTERISTIC / CARATTERISTICHE			
Battery dimensions / Dimensioni batteria			
L/L	W/P	H/A	Tot - H/A
181	77	167	167
Box Dimensions / Dimensioni scatola			
L/L	W/P	H/A	
341	195	213	
Weight / Peso		5.60Kg	
Terminal / Terminali		M5	
Case / Contenitore		ABS	

### Amp. (25°C)

F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	59.40	39.60	29.80	19.80	13.86	11.88	7.43	5.09	3.39	2.28	1.88	0.99
1.65V	58.32	38.88	29.25	19.44	13.61	11.66	7.29	5.00	3.33	2.24	1.85	0.97
1.70V	57.24	38.16	28.71	19.08	13.36	11.45	7.16	4.90	3.27	2.20	1.82	0.95
1.75V	56.16	37.44	28.17	18.72	13.10	11.23	7.02	4.81	3.21	2.16	1.78	0.94
1.80V	54.00	36.00	27.09	18.00	12.60	10.80	6.75	4.63	3.08	2.07	1.71	0.90

### Watts (25°C)


F.V/Time	5min	10min	15min	30min	45min	1h	2h	3h	5h	8h	10h	20h
1.60V	114.35	76.23	57.36	38.12	26.68	22.87	14.29	9.80	6.53	4.39	3.63	1.91
1.65V	112.27	74.84	56.31	37.42	26.20	22.45	14.03	9.62	6.41	4.31	3.56	1.87
1.70V	110.19	73.46	55.27	36.73	25.71	22.04	13.77	9.44	6.29	4.23	3.50	1.84
1.75V	108.11	72.07	54.23	36.04	25.23	21.62	13.51	9.26	6.17	4.15	3.43	1.80
1.80V	103.95	69.30	52.14	34.65	24.26	20.79	12.99	8.90	5.94	3.99	3.30	1.73

This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice. Contact U.B.S. UNION BATTERY SERVICE for the latest information.


Le informazioni contenute in questa scheda tecnica sono solo descrittive e indicative, non sono una garanzia. U.B.S. UNION BATTERY SERVICE si riserva il diritto di aggiornarle/modificarle senza preavviso.




[www.unionbatteryservice.it](http://www.unionbatteryservice.it)




## Charging characteristics



## Temperature effect on battery self-discharge



## Discharge characteristics (25°C)



## Temperature effect on capacity

